



NYCO
AERONAUTICS & DEFENCE



Product selection for T-72 and T-90 tanks

T-72 Light battle tank

Origins: Russia – Kirov

Type: A-1/A-1B-T/E – Air-Ground / Training

Power plant(s): RR SPEY MK807

T-90 Main battle tank

Origins: Russian – Uralvagonzavodu

Type: K/E/A/S/SK/M/MS

Power plant(s): V-12 diesel

The following products correspond to the non-exhaustive list of lubricants and ingredients available from NYCO. For any other requirements, do not hesitate to contact us.

PRODUCTS	GRADE	SPECIFICATIONS	DESCRIPTION
ENGINE OILS			
NYCOLUBE 14 Grade 16/A		GALOL M4042 TD M16 IKhP-3 GOST 25770-83	Petroleum lubricating oil for the lubrication of engines.
NYCOLUBE 14 Grade 16		GOST 6360-83 MT-16p	Petroleum lubricating oil for the lubrication of engines.
HYDRAULIC FLUIDS			
HYDRAUNYCOIL FH 55	POJ-70	TU-6-01-57575838-79	Synthetic hydraulic fluid used in ordnance circuits. Can be used in lieu of STEOL M.
HYDRAUNYCOIL FH 16	MGE-10A	OST 38 01281	Petroleum lubricating fluid for cars and machines system (-60°C +125°C).
GREASES			
NYCO GREASE GN 22	CIATIM 203	GOST 8773-73	Multipurpose synthetic grease for bearings, moving parts, gear and gyroscopic rotors.



Cage code F4101
+33 145 615 000
info@nyco.fr | www.nyco.fr

Continued next page



Product selection for T-72 and T-90 tanks

PRODUCTS	GRADE	SPECIFICATIONS	DESCRIPTION
GREASES			
NYCO GREASE GN 45	PFMS-4s	TU 6-02-917-79	Blend of a silicone and graphite, for the lubrication of roller bearings, transmissions in propellers and threadings up to 300°C.
NYCO GREASE GN 60	NK-50	TU 38 1011219-95	Petroleum lubricating grease with graphite. For the lubrication of wheel bearings in landing gear and inertia transmitter braking system.
NYCO GREASE GN 69	S-736 XG-250	AS 8660 DEF STAN 68-69 Iss.1	Filling compound in high tension electrical equipment and ignition systems (-54°C to +204°C).
NYCO GREASE GN 110	LITOL 24	GOST 21150-87	Multipurpose lithium mineral grease (-35°C to +135°C).
NYCO GREASE GN 116	SAPFIR VNII NP-261	TU 38.10111051-87	Synthetic grease for the lubrication of wheel bearings in landing gear and engine roller controls (-40°C to +150°C).
OTHER PRODUCTS			
NYCOLUBE 9	AU	GOST 38 01412 TU 38-101-1232-89	Pure petroleum base stock for the lubrication of spindles in special uses.
NYCOLUBE 20	K-17	GOST 10877-76	Petroleum protective oil, for the protection of stored mechanisms during a long period of time (five years).
NYCOLUBE 122	TSZp-8 MT-8P	TU 38-101280-89 TU 38-101277-85	Petroleum lubricating oil transmission fluid in planetary reduction gears; it is usable with a hot or temperate climate.